


Technical features:







- The number of pins varies according to the cylinder type
- CYLINDER
- brass body
- pins in wear resistant bronze
- drivers in brass, cylindrical and mushroom-like for an antipicking function
- phosphor bronze springs
- KEY
- nickel-plated brass









Supplied as standard:

- 2 or 3 keys
- Fixing screws

Finishes:

- Various finishes according to the cylinder type

Type	Description	Door thickness Pins	Key item	Unit weight Kg	Pieces	ITEM			
						Type	Dim.	Hand	Pers. Spec.
	• Cross-key cylinder complete with 19 mm adaptor • For locks series 16000, 46000 • Short key version	6	1 00210 00 0	0,119	1	1	02400	10	0
	• Cross-key cylinder complete with 19 mm adaptor • For locks series 16000, 46000 • Long key version	6	1 00211 00 0	0,132	1	1	02400	11	0
	• Cylinder for outside operation devices item 1.07077.28.0 • Sanded brass	5	1 01310 00 1	0,120	1	1	02649	10	0
	• Cylinder for outside operation devices item 1.07077.29.0 • Sanded brass	5	1 01310 00 1	0,118	1	1	02649	11	0
	• 3 keys • Belt sanded brass	4	1 01320 00 1	0,280	6	1	44010	02	0
	• 3 keys • Belt sanded brass	4	1 01320 00 1	0,280	6	1	44011	02	0
	• 2 keys • polished brass	4	1 01420 00 1	0,110	6	1	72010	00	0

Type	Description	Door thickness		Key item	Unit weight Kg	Pieces	ITEM				
		Pins					Type	Dim.	Hand	Fin.	Pers. Spec.
 	• 2 keys • Belt sanded brass • Key removed in vertical position • Cam item 06411 or 06412, to be ordered separately	11	3	1 01420 00 1	0,078	12	1	72210	16	0	
		15	4	1 01420 00 1	0,087	12	1	72210	20	0	
		20	4	1 01420 00 1	0,097	12	1	72210	25	0	
		25	4	1 01420 00 1	0,108	12	1	72210	30	0	
 	• MARINE TYPE • 2 keys • Chrome -plated brass • Key removed in vertical position • Cam item 1.06412.51.0, specify with order	11	3	1 01420 00 1	0,077	12	1	72215	16	0	
		15	4	1 01420 00 1	0,085	12	1	72215	20	0	
		20	4	1 01420 00 1	0,094	12	1	72215	25	0	
		25	4	1 01420 00 1	0,105	12	1	72215	30	0	
 	• Key removed in vertical position • Ring item 1.06021.10.0 • Cam item 1.06414.20.0 or item 1.06414.30.0, to be ordered separately	19	5	1 01310 00 1	0,135	6	1	72250	26	0	
	• 3 keys • Nickel-plated brass • Microswitch (7 A, 250 V) with terminals to be welded • Automatic return to key extraction position (0) • Ring item 1.06021.10.0	19	5	1 01310 00 1	0,145	6	1	72251	01	0	
	• 3 keys • Nickel-plated brass • Microswitch (7 A, 250 V) with terminals to be welded • Automatic return to key extraction position (0) • Ring item 1.06021.10.0	19	5	1 01310 00 1	0,144	6	1	72251	03	0	
 	• 2 keys • Special zinc alloy, stainless steel faceplate • Key removable in two positions • Cam item 06413 or 06414, to be ordered separately	8	5	1 01710 00 1	0,055	6	1	72350	17	0	
		16	5	1 01710 00 1	0,070	6	1	72350	25	0	