**Technical features:**

- 5 pins key biting system (4 pins for short size)
- 0,65 mm depth
- CYLINDER
- brass body
- brass plugs
- pins:
 - in wear resistant bronze
 - in hardened steel in first position
- drivers:
 - in brass, cylindrical and mushroom-like for an antipicking function
 - in hardened steel in first position
- phosphor bronze springs
- self-lubricating sintered steel projecting DIN cam
- KEY
- nickel-plated brass

Supplied as standard:

- 3 keys
- Fixing screw


Finishes:

- STANDARD:
- sanded brass (fin. 00)
- ON REQUEST:
- nickel-plated brass (fin. 12),
- polished brass (fin. 66)

Standards:




- Manufactured in conformity with EN 1303:
- Durability: grade 6 (100.000 cycles)
- Security: grade 2
- SKG** Certified (special version on request)

Type	Description	Comm. dim.				Key item			ITEM			
		L	A	B	Pins				Type	Dim.	Hand	Pers. Spec.
							Unit weight	Pieces				




• Double cylinder

25 / 25	49,8	24,9	24,9	4	1	01320 10 1	0,192	12	1	08710 04 0		
27 / 27	53,0	26,5	26,5	4	1	01320 10 1	0,202	12	1	08710 05 0		
27 / 33	59,0	26,5	32,5	4	1	01320 10 1	0,220	12	1	08710 06 0		
30 / 30	59,0	29,5	29,5	5	1	01310 10 1	0,220	12	1	08710 07 0		
30 / 33	62,0	29,5	32,5	5	1	01310 10 1	0,227	12	1	08710 08 0		
27 / 37	63,0	26,5	36,5	4	1	01320 10 1	0,234	12	1	08710 09 0		
30 / 35	64,0	29,5	34,5	5	1	01310 10 1	0,238	12	1	08710 26 0		
33 / 33	65,0	32,5	32,5	5	1	01310 10 1	0,237	12	1	08710 10 0		
27 / 43	69,0	26,5	42,5	4	1	01320 10 1	0,247	12	1	08710 11 0		
30 / 40	69,0	29,5	39,5	5	1	01310 10 1	0,249	12	1	08710 12 0		
35 / 35	69,0	34,5	34,5	5	1	01310 10 1	0,250	12	1	08710 13 0		
30 / 43	72,0	29,5	42,5	5	1	01310 10 1	0,260	6	1	08710 14 0		
37 / 37	73,0	36,5	36,5	5	1	01310 10 1	0,264	6	1	08710 15 0		
30 / 45	74,0	29,5	44,5	5	1	01310 10 1	0,275	6	1	08710 27 0		
35 / 40	74,0	34,5	39,5	5	1	01310 10 1	0,275	6	1	08710 28 0		
27 / 53	79,0	26,5	52,5	4	1	01320 10 1	0,281	6	1	08710 16 0		
30 / 50	79,0	29,5	49,5	5	1	01310 10 1	0,290	6	1	08710 17 0		
35 / 45	79,0	34,5	44,5	5	1	01310 10 1	0,290	6	1	08710 19 0		
40 / 40	79,0	39,5	39,5	5	1	01310 10 1	0,290	6	1	08710 18 0		
40 / 45	84,0	39,5	44,5	5	1	01310 10 1	0,303	6	1	08710 30 0		
43 / 43	85,0	42,5	42,5	5	1	01310 10 1	0,303	6	1	08710 46 0		
30 / 60	89,0	29,5	59,5	5	1	01310 10 1	0,316	6	1	08710 20 0		
40 / 50	89,0	39,5	49,5	5	1	01310 10 1	0,317	6	1	08710 21 0		
45 / 45	89,0	44,5	44,5	5	1	01310 10 1	0,317	6	1	08710 29 0		
30 / 70	99,0	29,5	69,5	5	1	01310 10 1	0,345	6	1	08710 24 0		
35 / 65	99,0	34,5	64,5	5	1	01310 10 1	0,345	6	1	08710 22 0		
40 / 60	99,0	39,5	59,5	5	1	01310 10 1	0,345	6	1	08710 25 0		
50 / 50	99,0	49,5	49,5	5	1	01310 10 1	0,345	6	1	08710 23 0		
30 / 80	109,0	29,5	79,5	5	1	01310 10 1	0,375	6	1	08710 37 0		
40 / 70	109,0	39,5	69,5	5	1	01310 10 1	0,375	6	1	08710 35 0		
50 / 60	109,0	49,5	59,5	5	1	01310 10 1	0,375	6	1	08710 36 0		

Type	Description	Comm. dim.				Key item	Kg	Unit weight	Pieces	ITEM				
		L	A	B	Pins					Type	Dim.	Hand	Fin.	Pers. Spec.
	• Clutching system double cylinder	27 / 27	54,0	27,0	27,0	4	1 01320 10 1	0,203	12	1	08714	05	0	
		27 / 33	59,5	27,0	32,5	4	1 01320 10 1	0,222	12	1	08714	06	0	
		31 / 31	61,6	30,8	30,8	5	1 01310 10 1	0,222	12	1	08714	07	0	
		31 / 35	65,3	30,8	34,5	5	1 01310 10 1	0,238	12	1	08714	26	0	
		27 / 43	69,5	27,0	42,5	4	1 01320 10 1	0,258	12	1	08714	11	0	
	• Single cylinder with adjustable cam in 8 position	30 / 10	39,5	29,5	10,0	5	1 01310 10 1	0,184	12	1	08730	02	0	
		33 / 10	42,5	32,5	10,0	5	1 01310 10 1	0,169	12	1	08730	09	0	
		35 / 10	44,5	34,5	10,0	5	1 01310 10 1	0,175	12	1	08730	07	0	
		37 / 10	46,5	36,5	10,0	5	1 01310 10 1	0,182	12	1	08730	10	0	
		40 / 10	49,5	39,5	10,0	5	1 01310 10 1	0,191	12	1	08730	03	0	
		43 / 10	52,5	42,5	10,0	5	1 01310 10 1	0,200	12	1	08730	11	0	
		50 / 10	59,5	49,5	10,0	5	1 01310 10 1	0,220	12	1	08730	04	0	
	• Double thumb turn cylinder with gold bronze aluminium anodized knob	27 / 27	54,0	27,0	27,0	4	1 01320 10 1	0,305	6	1	08728	02	0	
		31 / 23	54,0	30,8	23,2	5	1 01310 10 1	0,318	6	1	08728	03	0	
		27 / 33	59,5	27,0	32,5	4	1 01320 10 1	0,322	6	1	08728	24	0	
		33 / 27	59,5	32,5	27,0	5	1 01310 10 1	0,322	6	1	08728	05	0	
		31 / 31	61,6	30,8	30,8	5	1 01310 10 1	0,322	6	1	08728	04	0	
		31 / 33	63,3	30,8	32,5	5	1 01310 10 1	0,333	6	1	08728	07	0	
		33 / 31	63,3	32,5	30,8	5	1 01310 10 1	0,333	6	1	08728	06	0	
		31 / 37	67,1	30,8	36,3	5	1 01310 10 1	0,338	6	1	08728	09	0	
		37 / 31	67,1	36,3	30,8	5	1 01310 10 1	0,338	6	1	08728	10	0	
		31 / 43	73,3	30,8	42,5	5	1 01310 10 1	0,355	6	1	08728	11	0	
		43 / 31	73,3	42,5	30,8	5	1 01310 10 1	0,355	6	1	08728	12	0	
		31 / 50	80,8	30,8	50,0	5	1 01310 10 1	0,372	6	1	08728	26	0	
		36 / 46	82,1	36,3	45,8	5	1 01310 10 1	0,380	6	1	08728	19	0	
		33 / 50	82,5	32,5	50,0	5	1 01310 10 1	0,385	6	1	08728	29	0	
		43 / 43	85,0	42,5	42,5	5	1 01310 10 1	0,392	6	1	08728	25	0	
		43 / 46	88,3	42,5	45,8	5	1 01310 10 1	0,397	6	1	08728	21	0	
		46 / 43	88,3	45,8	42,5	5	1 01310 10 1	0,397	6	1	08728	22	0	
		31 / 60	90,8	30,8	60,0	5	1 01310 10 1	0,413	6	1	08728	27	0	
		31 / 80	110,8	30,8	80,0	5	1 01310 10 1	0,417	6	1	08728	13	0	
		27 / 85	112,0	27,0	85,0	4	1 01320 10 1	0,467	6	1	08728	28	0	

Type	Description	Comm. dim.				Key item	Kg	Unit weight	Pieces	ITEM				
		L	A	B	Pins					Type	Dim.	Hand	Fin.	Pers. Spec.



- Double cylinder with thumb turn shaft
- ON REQUEST: Knobs
item 1.06353.00
item 1.06354.00

27 / 27	54,0	27,0	27,0	4	1	01320 10 1	0,217	6	1	08753	02 0			
31 / 23	54,0	30,8	23,2	5	1	01310 10 1	0,230	6	1	08753	03 0			
27 / 33	59,5	27,0	32,5	4	1	01320 10 1	0,237	6	1	08753	24 0			
33 / 27	59,5	32,5	27,0	5	1	01310 10 1	0,237	6	1	08753	05 0			
31 / 31	61,6	30,8	30,8	5	1	01310 10 1	0,237	6	1	08753	04 0			
31 / 33	63,3	30,8	32,5	5	1	01310 10 1	0,247	6	1	08753	07 0			
33 / 31	63,3	32,5	30,8	5	1	01310 10 1	0,247	6	1	08753	06 0			
33 / 33	65,0	32,5	32,5	5	1	01310 10 1	0,250	6	1	08753	34 0			
43 / 23	65,7	42,5	23,2	5	1	01310 10 1	0,250	6	1	08753	41 0			
31 / 36	67,1	30,8	36,3	5	1	01310 10 1	0,267	6	1	08753	09 0			
36 / 31	67,1	36,3	30,8	5	1	01310 10 1	0,267	6	1	08753	10 0			
35 / 35	69,0	34,5	34,5	5	1	01310 10 1	0,275	6	1	08753	14 0			
36 / 36	72,6	36,3	36,3	5	1	01310 10 1	0,280	6	1	08753	18 0			
31 / 43	73,3	30,8	42,5	5	1	01310 10 1	0,283	6	1	08753	11 0			
43 / 31	73,3	42,5	30,8	5	1	01310 10 1	0,283	6	1	08753	12 0			
43 / 36	78,2	42,5	36,3	5	1	01310 10 1	0,280	6	1	08753	17 0			
31 / 50	80,8	30,8	50,0	5	1	01310 10 1	0,300	6	1	08753	26 0			
36 / 47	82,1	36,3	46,8	5	1	01310 10 1	0,308	6	1	08753	19 0			
47 / 36	82,1	46,8	36,3	5	1	01310 10 1	0,308	6	1	08753	33 0			
33 / 50	82,5	32,5	50,0	5	1	01310 10 1	0,317	6	1	08753	29 0			
43 / 43	85,0	42,5	42,5	5	1	01310 10 1	0,325	6	1	08753	25 0			
43 / 46	88,3	42,5	45,8	5	1	01310 10 1	0,333	6	1	08753	21 0			
46 / 43	88,3	45,8	42,5	5	1	01310 10 1	0,333	6	1	08753	22 0			
31 / 60	90,8	30,8	60,0	5	1	01310 10 1	0,342	6	1	08753	27 0			
68 / 23	91,2	68,0	23,2	5	1	01310 10 1	0,350	6	1	08753	42 0			
46 / 46	91,6	45,8	45,8	5	1	01310 10 1	0,350	6	1	08753	38 0			
60 / 36	96,3	60,0	36,3	5	1	01310 10 1	0,360	6	1	08753	37 0			
45 / 55	99,0	44,5	54,5	5	1	01310 10 1	0,370	6	1	08753	31 0			
55 / 45	99,0	54,5	44,5	5	1	01310 10 1	0,370	6	1	08753	35 0			
60 / 46	105,0	60,0	45,8	5	1	01310 10 1	0,385	6	1	08753	40 0			
60 / 50	110,0	60,0	50,0	5	1	01310 10 1	0,400	6	1	08753	39 0			
31 / 80	110,8	30,8	80,0	5	1	01310 10 1	0,400	6	1	08753	13 0			
27 / 85	112,0	27,0	85,0	4	1	01320 10 1	0,408	6	1	08753	28 0			
55 / 65	119,0	54,5	64,5	5	1	01310 10 1	0,430	6	1	08753	32 0			
65 / 55	119,0	64,5	54,5	5	1	01310 10 1	0,430	6	1	08753	36 0			