

**Technical features:**





- 5 pins key biting system
- 0,65 mm depth
- CYLINDER
- brass body
- brass plug
- pins:
  - in wear resistant bronze
  - in hardened steel in first position
- drivers:
  - in brass, cylindrical and mushroom-like for an antipicking function
  - in hardened steel in first position
- phosphor bronze springs
- KEY:
  - nickel-plated brass

**Supplied as standard:**

- 3 keys
- Fixing screw

**Finishes:**

- Nickel-plated brass

| Type                                                                                | Description                                                                                                                                                                                                                                              | Door thickness | Pins | Key item   | Unit weight | Pieces | ITEM |       |       |      |       |       |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|------|------------|-------------|--------|------|-------|-------|------|-------|-------|
|                                                                                     |                                                                                                                                                                                                                                                          |                |      |            | Kg          |        | Type | Dim.  | Hand  | Fin. | Pers. | Spec. |
|    | <ul style="list-style-type: none"><li>• Small cylinder for padlocks: series 28050 - 28350 - 28550</li><li>• 2 keys</li><li>• Pickled brass body</li><li>• Complete with plate item 1.07573.01.0</li></ul>                                                | 5              | 1    | 01310 10 1 | 0,095       | 6      | 1    | 02649 | 01    | 0    |       |       |
|                                                                                     |                                                                                                                                                                                                                                                          | 5              | 1    | 00401 00 1 | 0,096       | 6      | 1    | 02650 | 01    | 0    |       |       |
|  | <ul style="list-style-type: none"><li>• Key removed in vertical position</li><li>• Ring item 1.06021.10.0</li><li>• Cam item 1.06414.20.0 or item 1.06414.30.0, specify with order</li><li>• ON REQUEST: Microswitch support item 1.06422.10.0</li></ul> | 19             | 5    | 1          | 01310 10 1  | 0,160  | 6    | 1     | 72255 | 26   | 0     |       |
|                                                                                     |                                                                                                                                                                                                                                                          |                |      |            |             |        |      |       |       |      |       |       |
|  | <ul style="list-style-type: none"><li>• Microswitch (7 A, 250 V) with terminals to be welded</li><li>• Automatic return to key extraction position (0)</li><li>• Ring item 1.06021.10.0</li></ul>                                                        | 19             | 5    | 1          | 01310 10 1  | 0,156  | 6    | 1     | 72256 | 01   | 0     |       |
|                                                                                     |                                                                                                                                                                                                                                                          |                |      |            |             |        |      |       |       |      |       |       |
|  | <ul style="list-style-type: none"><li>• Microswitch (7 A, 250 V) with terminals to be welded</li><li>• Automatic return to key extraction position (0)</li><li>• Ring item 1.06021.10.0</li></ul>                                                        | 19             | 5    | 1          | 01310 10 1  | 0,157  | 6    | 1     | 72256 | 03   | 0     |       |
|                                                                                     |                                                                                                                                                                                                                                                          |                |      |            |             |        |      |       |       |      |       |       |