

AP3 EUROPEAN PROFILE CYLINDERS



Technical features:

- Patented system: key with incorporated mobile element
- Security Card: authorised duplication by Cisa or Cisa Solution Partner
- 12 pins (6+1 active, 5 passive) key biting system
- CYLINDER:
 - brass body
 - brass plugs
- pins:
 - in hardened steel, in a special anti-picking shape
- drivers:
 - in hardened steel, cylindrical and mushroom-like for anti-picking function
- phosphor bronze springs

- self-lubricating sintered steel projecting DIN cam
- KEY:
 - flat reversible keys, with incorporated mobile element
 - in nickel silver
 - numbered on key bow
 - long key for protective roses compatibility

Supplied as standard:

- 3 keys
- SECURITY CARD
- Fixing screw

On request:

- Cylinder with ALI key (pers. CL)

Finishes:

- STANDARD: nickel-plated brass (fin. 12)
- ON REQUEST: polished brass (fin. 66)


Standards:

- Manufactured in conformity with EN 1303:
- Durability: grade 6 (100.000 cycles)
- Security: grade 4
- ICIM Certified: EN1303:98 1600014
- SKG** Certified

Patents:

- PCT/EP99/07611
- ALI is a registered shape, file number 4.137.601

Type	Description	Comm. dim.	Key item				Unit weight	Pieces	ITEM				
			L	A	B	Pins			Type	Dim.	Hand	Fin.	Pers. Spec.



- Single cylinder with adjustable cam in 8 position

30 / 10	39,5	29,5	10,0	12	1	00770 00 0	0,185	1	1	0H314 02 0 12
35 / 10	44,5	34,5	10,0	12	1	00770 00 0	0,195	1	1	0H314 07 0 12
40 / 10	49,5	39,5	10,0	12	1	00770 00 0	0,215	1	1	0H314 03 0 12
45 / 10	54,5	44,5	10,0	12	1	00770 00 0	0,225	1	1	0H314 08 0 12
50 / 10	59,5	49,5	10,0	12	1	00770 00 0	0,245	1	1	0H314 04 0 12
60 / 10	69,5	59,5	10,0	12	1	00770 00 0	0,275	1	1	0H314 05 0 12
65 / 10	74,5	64,5	10,0	12	1	00770 00 0	0,290	1	1	0H314 21 0 12
70 / 10	79,5	69,5	10,0	12	1	00770 00 0	0,305	1	1	0H314 06 0 12
80 / 10	89,5	79,5	10,0	12	1	00770 00 0	0,330	1	1	0H314 20 0 12
95 / 10	104,5	94,5	10,0	12	1	00770 00 0	0,380	1	1	0H314 13 0 12