








	Technical features: • Patented system: key with incorporated mobile element • Security Card: authorised duplication by Cisa or Cisa Solution Partner • 12 pins (6+1 active, 5 passive) key biting system • CYLINDER • brass body • brass plug • pins: - in hardened steel, in a special anti-picking shape • drivers: - in hardened steel, cylindrical and mushroom-like for anti-picking function • phosphor bronze springs • KEY: - flat reversible keys, with incorporated mobile element Supplied as standard: • 3 keys • SECURITY CARD • Fixing screw On request: • Cylinder with ALI key (pers. CL) Finishes: • Nickel-plated brass (Fin. 12) Patents: • PCT/EP99/07611 • ALI is a registered shape, file number 4.137.601
--	---

Type	Description	Door thickness	Pins	Key item	Unit weight	Pieces	ITEM Type Dim. Hand. Fin. Pers. Spec.
	• Small cylinder for steel padlocks • 2 keys • Pickled brass body • Complete with plate item 1.07573.08.0	12	1	1 00770 00 0	0,117	1 1	0H610 00 0
	• Cylinder for outside operation devices item 1.07077.28.0 • Sanded brass	12	1	1 00770 00 0	0,117	1 1	0H610 10 0
	• Cylinder for outside operation devices item 1.07077.29.0 • Sanded brass	12	1	1 00770 00 0	0,117	1 1	0H610 11 0
	• Cylinder for premi/apri locks	12	1	1 00770 00 0	0,117	1 1	0H610 12 0 12
	• Key removed in vertical position • Ring item 1.06021.10.0 • Cam item 1.06414.20.0 or item 1.06414.30.0 to be ordered separately	19	12	1 00770 00 0	0,150	1 1	0H410 00 0 12
	• Microswitch (7 A, 250 V) with terminals to be welded • Automatic return to key extraction position (0) • Ring item 1.06021.10.0	19	12	1 00770 00 0	0,150	1 1	0H415 01 0 12

Type	Description	Door thickness		Key item	Unit weight	Pieces	ITEM				
		Pins					Type	Dim.	Hand	Fin.	Pers. Spec.
	• Microswitch (7 A, 250 V) with terminals to be welded • Automatic return to key extraction position (0) • Ring item 1.06021.10.0	19	12	1 00770 00 0	0,150	1	1	0H415	03	0	12