

Technical features:

- 6 pins key biting system
- CYLINDER
- brass body
- brass plugs
- pins:
 - in wear resistant bronze
 - in hardened steel in first position
- drivers:
 - in brass
 - in hardened steel in first position
- phosphor bronze springs
- self-lubricating sintered steel projecting cam, DIN-compatible
- KEY:
 - flat reversible keys
 - in nickel-plated brass
 - long key for protective roses compatibility

Supplied as standard:

- 3 keys
- Fixing screw


Finishes:

- STANDARD: sanded brass (fin. 00)
- ON REQUEST:
 - nickel-plated brass (fin. 12)
 - polished brass (fin. 66)

Standards:

- Manufactured in conformity with EN 1303:
- Durability: grade 6 (100.000 cycles)
- Security: grade 3


Type	Description	Comm. dim.	Key item				Kg	Pieces	ITEM			
			L	A	B	Pins			Type	Dim.	Hand	Pers. Spec.



• Double cylinder


28 / 28	55,4	27,7	27,7	6	1	00670 01 0	0,216	6	1	OE300	05 0	
30 / 30	59,0	29,5	29,5	6	1	00670 01 0	0,223	6	1	OE300	07 0	
28 / 32	59,2	27,7	31,5	6	1	00670 01 0	0,225	6	1	OE300	08 0	
28 / 34	61,2	27,7	33,5	6	1	00670 01 0	0,230	6	1	OE300	06 0	
28 / 36	63,2	27,7	35,5	6	1	00670 01 0	0,242	6	1	OE300	09 0	
30 / 35	64,0	29,5	34,5	6	1	00670 01 0	0,233	6	1	OE300	26 0	
33 / 33	65,0	32,5	32,5	6	1	00670 01 0	0,242	6	1	OE300	10 0	
35 / 35	69,0	34,5	34,5	6	1	00670 01 0	0,267	6	1	OE300	13 0	
40 / 30	69,0	39,5	29,5	6	1	00670 01 0	0,258	6	1	OE300	12 0	
28 / 43	70,2	27,7	42,5	6	1	00670 01 0	0,275	6	1	OE300	11 0	
30 / 45	74,0	29,5	44,5	6	1	00670 01 0	0,264	6	1	OE300	27 0	
35 / 40	74,0	34,5	39,5	6	1	00670 01 0	0,264	6	1	OE300	28 0	
30 / 50	79,0	29,5	49,5	6	1	00670 01 0	0,279	6	1	OE300	17 0	
35 / 45	79,0	34,5	44,5	6	1	00670 01 0	0,279	6	1	OE300	19 0	
40 / 40	79,0	39,5	39,5	6	1	00670 01 0	0,279	6	1	OE300	18 0	
30 / 55	84,0	29,5	54,5	6	1	00670 01 0	0,294	6	1	OE300	33 0	
35 / 50	84,0	34,5	49,5	6	1	00670 01 0	0,294	6	1	OE300	31 0	
40 / 45	84,0	39,5	44,5	6	1	00670 01 0	0,294	6	1	OE300	30 0	
30 / 60	89,0	29,5	59,5	6	1	00670 01 0	0,310	6	1	OE300	20 0	
35 / 55	89,0	34,5	54,5	6	1	00670 01 0	0,310	6	1	OE300	32 0	
40 / 50	89,0	39,5	49,5	6	1	00670 01 0	0,310	6	1	OE300	21 0	
45 / 45	89,0	44,5	44,5	6	1	00670 01 0	0,310	6	1	OE300	29 0	
30 / 65	94,0	29,5	64,5	6	1	00670 01 0	0,324	6	1	OE300	41 0	
35 / 60	94,0	34,5	59,5	6	1	00670 01 0	0,324	6	1	OE300	38 0	
40 / 55	94,0	39,5	54,5	6	1	00670 01 0	0,324	6	1	OE300	42 0	
45 / 50	94,0	44,5	49,5	6	1	00670 01 0	0,324	6	1	OE300	39 0	
30 / 70	99,0	29,5	69,5	6	1	00670 01 0	0,339	6	1	OE300	24 0	
35 / 65	99,0	34,5	64,5	6	1	00670 01 0	0,339	6	1	OE300	22 0	
40 / 60	99,0	39,5	59,5	6	1	00670 01 0	0,339	6	1	OE300	25 0	
45 / 55	99,0	44,5	54,5	6	1	00670 01 0	0,339	6	1	OE300	43 0	
50 / 50	99,0	49,5	49,5	6	1	00670 01 0	0,339	6	1	OE300	23 0	
30 / 80	109,0	29,5	79,5	6	1	00670 01 0	0,368	6	1	OE300	37 0	
40 / 70	109,0	39,5	69,5	6	1	00670 01 0	0,368	6	1	OE300	35 0	
50 / 60	109,0	49,5	59,5	6	1	00670 01 0	0,368	6	1	OE300	36 0	
55 / 55	109,0	54,5	54,5	6	1	00670 01 0	0,368	6	1	OE300	70 0	
55 / 60	114,0	54,5	59,5	6	1	00670 01 0	0,368	6	1	OE300	71 0	
60 / 60	119,0	59,5	59,5	6	1	00670 01 0	0,368	6	1	OE300	40 0	

Type	Description	Comm. dim.					Key item	Kg	Unit weight	Pieces	ITEM				
		L	A	B	Pls						Type	Dim.	Hand	Fin.	Pers. Spec.




- Single cylinder with adjustable cam in 8 position

30 / 10	39,5	29,5	10,0	6	1	00670 01 0	0,164	6	1	0E304 02 0
35 / 10	44,5	34,5	10,0	6	1	00670 01 0	0,179	6	1	0E304 07 0
37 / 10	46,5	36,5	10,0	6	1	00670 01 0	0,185	6	1	0E304 10 0
40 / 10	49,5	39,5	10,0	6	1	00670 01 0	0,195	6	1	0E304 03 0
45 / 10	54,5	44,5	10,0	6	1	00670 01 0	0,207	6	1	0E304 08 0
50 / 10	59,5	49,5	10,0	6	1	00670 01 0	0,222	6	1	0E304 04 0
60 / 10	69,5	59,5	10,0	6	1	00670 01 0	0,252	6	1	0E304 05 0
65 / 10	74,5	64,5	10,0	6	1	00670 01 0	0,267	6	1	0E304 21 0
70 / 10	79,5	69,5	10,0	6	1	00670 01 0	0,282	6	1	0E304 06 0
80 / 10	89,5	79,5	10,0	6	1	00670 01 0	0,312	6	1	0E304 20 0




- Double cylinder with thumb turn shaft
- ON REQUEST: Knobs
item 1.06353.00
item 1.06354.00

30 / 30	59,0	29,5	29,5	6	1	00670 01 0	0,239	6	1	0E302 07 0
30 / 35	64,0	29,5	34,5	6	1	00670 01 0	0,254	6	1	0E302 26 0
35 / 30	64,0	34,5	29,5	6	1	00670 01 0	0,254	6	1	0E302 81 0
30 / 40	69,0	29,5	39,5	6	1	00670 01 0	0,274	6	1	0E302 82 0
35 / 35	69,0	34,5	34,5	6	1	00670 01 0	0,274	6	1	0E302 13 0
35 / 40	74,0	34,5	39,5	6	1	00670 01 0	0,289	6	1	0E302 28 0
30 / 50	79,0	29,5	49,5	6	1	00670 01 0	0,304	6	1	0E302 17 0
35 / 45	79,0	34,5	44,5	6	1	00670 01 0	0,304	6	1	0E302 19 0
40 / 40	79,0	39,5	39,5	6	1	00670 01 0	0,304	6	1	0E302 18 0
40 / 45	84,0	39,5	44,5	6	1	00670 01 0	0,319	6	1	0E302 30 0
45 / 40	84,0	44,5	39,5	6	1	00670 01 0	0,319	6	1	0E302 84 0
43 / 43	85,0	42,5	42,5	6	1	00670 01 0	0,321	6	1	0E302 46 0
30 / 60	89,0	29,5	59,5	6	1	00670 01 0	0,334	6	1	0E302 20 0
40 / 50	89,0	39,5	49,5	6	1	00670 01 0	0,334	6	1	0E302 21 0
40 / 55	94,0	39,5	54,5	6	1	00670 01 0	0,355	6	1	0E302 42 0
45 / 50	94,0	44,5	49,5	6	1	00670 01 0	0,355	6	1	0E302 39 0
45 / 55	99,0	44,5	54,5	6	1	00670 01 0	0,365	6	1	0E302 43 0
50 / 50	99,0	49,5	49,5	6	1	00670 01 0	0,365	6	1	0E302 23 0
45 / 60	104,0	44,5	59,5	6	1	00670 01 0	0,379	6	1	0E302 54 0
55 / 50	104,0	54,5	49,5	6	1	00670 01 0	0,379	6	1	0E302 64 0



- Nickel-plated double cylinder C2000 series with special cam 90° for series 46305 locks

30 / 30	59,0	29,5	29,5	6			0,225	6	1	0E303 07 0 12
---------	------	------	------	---	--	--	-------	---	---	---------------



- Nickel-plated single cylinder C2000 series with special cam 90° for series 46305 locks

30 / 10	39,5	29,5	10,0	6			0,164	6	1	0E305 02 0 12
---------	------	------	------	---	--	--	-------	---	---	---------------