


ASTRAL
Technical features:







- 10 (6 active + 4 passive) pins key biting system
- CYLINDER:
 - brass body
 - brass plug
- pins:
 - in wear resistant bronze
 - in hardened steel in first position
- drivers:
 - in brass
 - in hardened steel in first position
- phosphor bronze springs
- KEY:
 - flat reversible keys
 - in nickel-plated brass
 - numbered on key bow

Supplied as standard:

- 3 keys
- Code Card
- Fixing screws

Finishes:

- Nickel-plated brass (fin. 12)

Type	Description	Door thickness Pins	Key item	Unit weight Kg	Pieces	ITEM				
						Type	Dim.	Hand	Fin.	Pers. Spec.
	• Small cylinder for padlocks: series 28053 - 28353 - 28553 • 2 keys • Pickled brass body • Complete with plate item 1.07573.08.0	10	1 00620 01 0	0,106	6	1	0A610	00	0	
	• Cylinder for outside operation devices item 1.07077.28.0 • Sanded brass	10	1 00620 01 0	0,106	6	1	0A610	10	0	
	• Cylinder for outside operation devices item 1.07077.29.0 • Sanded brass	10	1 00620 01 0	0,106	6	1	0A610	11	0	
	• Key removed in vertical position • Ring item 1.06021.10.0 • Cam item 1.06414.20.0 or item 1.06414.30.0, to be ordered separately	19	10 1 00620 01 0	0,195	1	1	0A410	00	0	
	• Microswitch (7 A, 250 V) with terminals to be welded • Automatic return to key extraction position (0) • Ring item 1.06021.10.0	19	10 1 00620 01 0	0,140	1	1	0A415	01	0	
	• Microswitch (7 A, 250 V) with terminals to be welded • Automatic return to key extraction position (0) • Ring item 1.06021.10.0	19	10 1 00620 01 0	0,188	1	1	0A415	03	0	