**Technical features:**

- 5 pins key biting system (3, 4 pins for short size)
- 0,44 mm depth
- CYLINDER:
 - brass body
 - brass plugs
 - pins:
 - in brass
 - in hardened steel in first position
 - drivers:
 - in brass, cylindrical and mushroom-like for an antipicking function
 - in hardened steel in first position
 - phosphor bronze springs
 - self-lubricating sintered steel projecting cam, DIN-compatible

- KEY
 - nickel-plated brass
 - long key for protective roses compatibility

Supplied as standard:

- 3 keys
- Fixing screw

On request:


- Standard DIN cam pers. 70




Finishes:

- STANDARD: sanded brass (fin. 00)
- ON REQUEST: nickel-plated brass (fin. 12)


Standards:


- Manufactured in conformity with EN 1303:
- Durability: grade 6 (100.000 cycles)
- Security: grade 3


Type	Description	Comm. dim.				Key item	Kg	Pieces	ITEM				
		L	A	B	Pins				Type	Dim.	Hand	Fin.	Pers. Spec.
	• Double cylinder	22 / 22	43,4	21,7	21,7	3	1 01070 01 1	0,172	12	1	OG300	02 0	
		22 / 27	48,4	21,7	26,7	3	1 01070 01 1	0,192	12	1	OG300	03 0	
		25 / 25	49,8	24,9	24,9	4	1 01070 05 1	0,189	12	1	OG300	04 0	
		27 / 27	53,0	26,5	26,5	4	1 01070 05 1	0,200	12	1	OG300	05 0	
		27 / 33	59,0	26,5	32,5	4	1 01070 05 1	0,216	12	1	OG300	06 0	
		30 / 30	59,0	29,5	29,5	5	1 01070 10 1	0,216	12	1	OG300	07 0	
		30 / 33	62,0	29,5	32,5	5	1 01070 10 1	0,212	12	1	OG300	08 0	
		27 / 37	63,0	26,5	36,5	4	1 01070 05 1	0,237	12	1	OG300	09 0	
		30 / 35	64,0	29,5	34,5	5	1 01070 10 1	0,233	12	1	OG300	26 0	
		33 / 33	65,0	32,5	32,5	5	1 01070 10 1	0,233	12	1	OG300	10 0	
		27 / 43	69,0	26,5	42,5	4	1 01070 05 1	0,250	12	1	OG300	11 0	
		30 / 40	69,0	29,5	39,5	5	1 01070 10 1	0,250	12	1	OG300	12 0	
		35 / 35	69,0	34,5	34,5	5	1 01070 10 1	0,250	12	1	OG300	13 0	
		30 / 43	72,0	29,5	42,5	5	1 01070 10 1	0,258	6	1	OG300	14 0	
		37 / 37	73,0	36,5	36,5	5	1 01070 10 1	0,266	6	1	OG300	15 0	
		30 / 45	74,0	29,5	44,5	5	1 01070 10 1	0,266	6	1	OG300	27 0	
		35 / 40	74,0	34,5	39,5	5	1 01070 10 1	0,266	6	1	OG300	28 0	
		27 / 53	79,0	26,5	52,5	4	1 01070 05 1	0,283	6	1	OG300	16 0	
		30 / 50	79,0	29,5	49,5	5	1 01070 10 1	0,291	6	1	OG300	17 0	
		35 / 45	79,0	34,5	44,5	5	1 01070 10 1	0,283	6	1	OG300	19 0	
		40 / 40	79,0	39,5	39,5	5	1 01070 10 1	0,285	6	1	OG300	18 0	
		35 / 50	84,0	34,5	49,5	5	1 01070 10 1	0,300	6	1	OG300	31 0	
		40 / 45	84,0	39,5	44,5	5	1 01070 10 1	0,300	6	1	OG300	30 0	
		43 / 43	85,0	42,5	42,5	5	1 01070 10 1	0,303	6	1	OG300	46 0	
		30 / 60	89,0	29,5	59,5	5	1 01070 10 1	0,316	6	1	OG300	20 0	
		35 / 55	89,0	34,5	54,5	5	1 01070 10 1	0,325	12	1	OG300	32 0	
		40 / 50	89,0	39,5	49,5	5	1 01070 10 1	0,316	6	1	OG300	21 0	
		45 / 45	89,0	44,5	44,5	5	1 01070 10 1	0,325	6	1	OG300	29 0	
		40 / 55	94,0	39,5	54,5	5	1 01070 10 1	0,292	6	1	OG300	42 0	
		30 / 70	99,0	29,5	69,5	5	1 01070 10 1	0,350	6	1	OG300	24 0	
		35 / 65	99,0	34,5	64,5	5	1 01070 10 1	0,312	6	1	OG300	22 0	
		40 / 60	99,0	39,5	59,5	5	1 01070 10 1	0,350	6	1	OG300	25 0	
		45 / 55	99,0	44,5	54,5	5	1 01070 10 1	0,312	6	1	OG300	43 0	
		50 / 50	99,0	49,5	49,5	5	1 01070 10 1	0,350	6	1	OG300	23 0	
		45 / 60	104,0	44,5	59,5	5	1 01070 10 1	0,350	6	1	OG300	54 0	
		30 / 80	109,0	29,5	79,5	5	1 01070 10 1	0,350	6	1	OG300	37 0	
		40 / 70	109,0	39,5	69,5	5	1 01070 10 1	0,360	6	1	OG300	35 0	
		50 / 60	109,0	49,5	59,5	5	1 01070 10 1	0,360	6	1	OG300	36 0	
		55 / 55	109,0	54,5	54,5	5	1 01070 10 1	0,360	6	1	OG300	70 0	
		60 / 60	119,0	59,5	59,5	5	1 01070 10 1	0,390	6	1	OG300	40 0	
		70 / 70	139,0	69,5	69,5	5	1 01070 10 1	0,440	6	1	OG300	50 0	

Type	Description	Comm. dim.				Key item	 Kg		ITEM				
		L	A	B	Pins				Type	Dim.	Hand	Fin.	Pers. Spec.
	• Clutching system double cylinder	27 / 27	53,0	26,5	26,5	4	1	01070 05 1	0,202	12	1	OG301 05 0	
		27 / 33	59,0	26,5	32,5	4	1	01070 05 1	0,222	12	1	OG301 06 0	
		30 / 30	59,0	29,5	29,5	5	1	01070 10 1	0,222	12	1	OG301 07 0	
		27 / 37	63,0	26,5	36,5	4	1	01070 05 1	0,232	12	1	OG301 09 0	
		30 / 35	64,0	29,5	34,5	5	1	01070 10 1	0,232	12	1	OG301 26 0	
		27 / 43	69,0	26,5	42,5	4	1	01070 05 1	0,252	12	1	OG301 11 0	
		35 / 35	69,0	34,5	34,5	5	1	01070 10 1	0,252	12	1	OG301 13 0	
		30 / 40	69,0	29,5	39,5	5	1	01070 10 1	0,252	12	1	OG301 12 0	
		35 / 40	74,0	34,5	39,5	5	1	01070 10 1	0,252	12	1	OG301 28 0	
		40 / 45	84,0	39,5	44,5	5	1	01070 10 1	0,252	12	1	OG301 30 0	
	• Single cylinder with adjustable cam in 8 position	25 / 10	34,5	24,5	10,0	4	1	01070 05 1	0,120	12	1	OG304 18 0	
		30 / 10	39,5	29,5	10,0	5	1	01070 10 1	0,155	12	1	OG304 02 0	
		33 / 10	42,5	32,5	10,0	5	1	01070 10 1	0,165	12	1	OG304 09 0	
		35 / 10	44,5	34,5	10,0	5	1	01070 10 1	0,170	12	1	OG304 07 0	
		37 / 10	46,5	36,5	10,0	5	1	01070 10 1	0,175	12	1	OG304 10 0	
		40 / 10	49,5	39,5	10,0	5	1	01070 10 1	0,191	12	1	OG304 03 0	
		43 / 10	52,5	42,5	10,0	5	1	01070 10 1	0,195	12	1	OG304 11 0	
		50 / 10	59,5	49,5	10,0	5	1	01070 10 1	0,215	12	1	OG304 04 0	
		55 / 10	64,5	54,5	10,0	5	1	01070 10 1	0,245	12	1	OG304 35 0	
		60 / 10	69,5	59,5	10,0	5	1	01070 10 1	0,245	12	1	OG304 05 0	
		64 / 10	73,5	63,5	10,0	5	1	01070 10 1	0,255	12	1	OG304 21 0	
		70 / 10	79,5	69,5	10,0	5	1	01070 10 1	0,275	12	1	OG304 06 0	
		80 / 10	89,5	79,5	10,0	5	1	01070 10 1	0,305	12	1	OG304 20 0	
		94 / 10	103,5	93,5	10,0	5	1	01070 10 1	0,355	12	1	OG304 13 0	
	• Double cylinder with thumb turn shaft • ON REQUEST: Knobs item 1.06353.00 item 1.06354.00	30 / 30	59,0	29,5	29,5	5	1	01070 10 1	0,237	6	1	OG302 07 0	
		30 / 35	64,0	29,5	34,5	5	1	01070 10 1	0,250	6	1	OG302 26 0	
		35 / 30	64,0	34,5	29,5	5	1	01070 10 1	0,250	6	1	OG302 81 0	
		33 / 33	65,0	32,5	32,5	5	1	01070 10 1	0,255	6	1	OG302 10 0	
		30 / 40	69,0	29,5	39,5	5	1	01070 10 1	0,270	6	1	OG302 82 0	
		35 / 35	69,0	34,5	34,5	5	1	01070 10 1	0,270	6	1	OG302 13 0	
		40 / 30	69,0	39,5	29,5	5	1	01070 10 1	0,270	6	1	OG302 12 0	
		35 / 40	74,0	34,5	39,5	5	1	01070 10 1	0,285	6	1	OG302 28 0	
		40 / 35	74,0	39,5	34,5	5	1	01070 10 1	0,285	6	1	OG302 83 0	
		30 / 50	79,0	29,5	49,5	5	1	01070 10 1	0,300	6	1	OG302 17 0	
		35 / 45	79,0	34,5	44,5	5	1	01070 10 1	0,300	6	1	OG302 19 0	
		40 / 40	79,0	39,5	39,5	5	1	01070 10 1	0,300	6	1	OG302 18 0	
		45 / 35	79,0	44,5	34,5	5	1	01070 10 1	0,300	6	1	OG302 85 0	
		40 / 45	84,0	39,5	44,5	5	1	01070 10 1	0,315	6	1	OG302 30 0	
		45 / 40	84,0	44,5	39,5	5	1	01070 10 1	0,315	6	1	OG302 84 0	
		43 / 43	85,0	42,5	42,5	5	1	01070 10 1	0,318	6	1	OG302 46 0	
		30 / 60	89,0	29,5	59,5	5	1	01070 10 1	0,330	6	1	OG302 20 0	
		40 / 50	89,0	39,5	49,5	5	1	01070 10 1	0,330	6	1	OG302 21 0	
		45 / 45	89,0	44,5	44,5	5	1	01070 10 1	0,330	6	1	OG302 29 0	
		40 / 55	94,0	39,5	54,5	5	1	01070 10 1	0,350	6	1	OG302 42 0	
		45 / 50	94,0	44,5	49,5	5	1	01070 10 1	0,350	6	1	OG302 39 0	
		45 / 55	99,0	44,5	54,5	5	1	01070 10 1	0,360	6	1	OG302 43 0	
		50 / 50	99,0	49,5	49,5	5	1	01070 10 1	0,360	6	1	OG302 23 0	
		45 / 60	104,0	44,5	59,5	5	1	01070 10 1	0,375	6	1	OG302 54 0	
		55 / 50	104,0	54,5	49,5	5	1	01070 10 1	0,375	6	1	OG302 64 0	
		30 / 80	109,0	29,5	79,5	5	1	01070 10 1	0,390	6	1	OG302 37 0	
		40 / 70	109,0	39,5	69,5	5	1	01070 10 1	0,390	6	1	OG302 35 0	
		50 / 60	109,0	49,5	59,5	5	1	01070 10 1	0,390	6	1	OG302 36 0	
		60 / 50	109,0	59,5	49,5	5	1	01070 10 1	0,390	6	1	OG302 89 0	
		55 / 60	114,0	54,5	59,5	5	1	01070 10 1	0,400	6	1	OG302 71 0	
		55 / 65	119,0	54,5	64,5	5	1	01070 10 1	0,420	6	1	OG302 72 0	
		60 / 60	119,0	59,5	59,5	5	1	01070 10 1	0,420	6	1	OG302 40 0	
		65 / 55	119,0	64,5	54,5	5	1	01070 10 1	0,420	6	1	OG302 86 0	

Type	Description	Comm. dim.				Key item			ITEM				
		L	A	B	Pins				Type	Dim.	Hand	Fin.	Pers. Spec.

	• Double cylinder with adjustable thumb turn shaft	30 / 30	59,0	29,5	29,5	5	1 01070 10 1	0,260	6	1	0G307 07 0		
		35 / 30	64,0	34,5	29,5	5	1 01070 10 1	0,270	6	1	0G307 81 0		
	• To be combined with inside rose item 1.06458.20	40 / 30	69,0	39,5	29,5	5	1 01070 10 1	0,280	6	1	0G307 12 0		
		45 / 30	74,0	44,5	29,5	5	1 01070 10 1	0,290	6	1	0G307 91 0		
	• ON REQUEST:Knobs	50 / 30	79,0	49,5	29,5	5	1 01070 10 1	0,300	6	1	0G307 90 0		
	item 1.06353.00	60 / 30	89,0	59,5	29,5	5	1 01070 10 1	0,320	6	1	0G307 87 0		
	item 1.06354.00	70 / 30	99,0	69,5	29,5	5	1 01070 10 1	0,340	6	1	0G307 88 0		

	• Nickel-plated double cylinder C2000 series with special cam 90° for series 46305 locks	30 / 30	59,0	29,5	29,5	5	1 01070 10 1	0,216	12	1	0G303 07 0 12		
---	--	----------------	------	------	------	---	--------------	-------	----	---	----------------------	--	--

	• Nickel-plated double cylinder C2000 series with special cam 90° for series 46305 locks	30 / 10	39,5	29,5	10,0	5		0,155	12	1	0G305 02 0 12		
--	--	----------------	------	------	------	---	--	-------	----	---	----------------------	--	--