

**Technical features:**

- Zinc plated steel faceplate
- Zinc plated steel case
- Nickel-plated reversible steel latch with anti-picking device
- Single throw (15 mm.) nickel-plated dead-bolt
- 9 mm. through follower

Supplied as standard:


- Instruction sheet

Hand:

0 = Non-handed

**Cylinder to
be ordered
separately**


Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight 	 Pieces	ITEM			
								Type	Dim. Hand	Fin.	Pers. Spec.



- Dead-bolt and latch

• OPERATION:

Outside and inside: latch and dead-bolt operated by key; latch withdrawn by handle

1	92	24	25	0,680	1	1	43520 25 0
1	92	24	30	0,720	1	1	43520 30 0
1	92	24	35	0,775	1	1	43520 35 0
1	92	24	40	0,805	1	1	43520 40 0
1	92	24	45	1,000	1	1	43520 45 0

- Dead-bolt and latch

• OPERATION:

Outside and inside: the key operates the dead-bolt and activates or disactivates the handle for latch operation

1	92	24	25	0,680	1	1	43530 25 0
1	92	24	30	0,720	1	1	43530 30 0
1	92	24	35	0,775	1	1	43530 35 0
1	92	24	40	0,805	1	1	43530 40 0
1	92	24	45	1,000	1	1	43530 45 0