

**Technical features:**

- Geared operating device for reducing key effort
- Zinc plated steel case
- Nickel-plated satin steel faceplate
- Nickel-plated reversible latch
- Nickel-plated steel dead-bolts
- Packing: 1 or 5 pcs. (industrial wrapping)


Hand:

0 = Non-handed

Cylinder to
be ordered
separately


**REVOLUTION**

Type	Description	DEAD-BOLTS							ITEM				
		No.	Projection Distance	Throws	Centre Distance	Faceplate Backset	Unit weight Kg	Pieces	Type	Dim. Hand	Fin.	Pers. Spec.	




- Dead-bolt and latch
- Electrically controlled dead-locking latch
- 12 V ac CE
- Slide item 1.06224.50.0

4	28	2	85	35	67	2,600	1	1	15530	28	0	
4	28	2	85	35	67	2,300	5	1	15530	48	0	








- Dead-bolt and latch
- Electrically controlled dead-locking latch
- 12 V ac CE
- Slide item 1.06224.50.0
- Pre-arranged for additional locking points

4	28	2	85	35	67	2,790	1	1	15535	28	0	
4	28	2	85	35	67	2,490	5	1	15535	48	0	



- Dead-bolt only

5	28	2	85	35	67	2,550	1	1	56520	28	0	
5	28	2	85	35	67	2,250	5	1	56520	48	0	

Type	Description	DEAD-BOLTS								ITEM				
		No.	Projection	Distance	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	Type	Dim.	Hand	Fin.
	• Dead-bolt only • Pre-arranged for additional locking points	5	28	2	85	35	67	2,650	1	1	56525 28 0			
		5	28	2	85	35	67	2,350	5	1	56525 48 0			
	• Dead-bolt and latch	4	28	2	85	35	67	2,420	1	1	56530 28 0			
		4	28	2	85	35	67	2,120	5	1	56530 48 0			
	• Dead-bolt and latch • Pre-arranged for additional locking points	4	28	2	85	35	67	2,800	1	1	56535 28 0			
		4	28	2	85	35	67	2,600	5	1	56535 48 0			
	• Dead-bolt only • Pre-arranged for additional locking points	5	28	2	85	35	67	2,650	1	1	B6525 28 0			
		5	38	2	85	35	67	2,650	1	1	B6525 38 0			
		5	28	2	85	35	67	2,350	1	1	B6525 48 0			
		5	38	2	85	35	67	2,350	1	1	B6525 58 0			
	• Dead-bolt and latch • Pre-arranged for additional locking points	4	28	2	85	35	67	3,100	1	1	B6535 28 0			
		4	38	2	85	35	67	2,600	1	1	B6535 38 0			
		4	28	2	85	35	67	2,300	1	1	B6535 48 0			
		4	38	2	85	35	67	2,300	1	1	B6535 58 0			