

**SMART****Technical features:**






- Aluminium alloy monoblock body
- Nylon case cover.
- Steel arm with or without adjustable hold open
- Special oil bath steel spring
- Valve with thermostatic device
- Adjustments
- Closing strength 2÷6
- Adjustable closing speed
- Latch action
- Regulation of door hold open (series 71411)




Supplied as standard:

- Fixing screws
- Template and assembly instructions.

Finishes:

- Always specify the finish on the orders
- Possible finishes at no extra cost
CHAMPAGNE colour (fin. 87)
DARK BROWN colour (fin. 88)
ALUMINIUM colour (fin. 97)
DARK BRONZE colour (fin. 99)
- Possible finishes at an extra cost
RED colour (fin. 41)
YELLOW colour (fin. 42)
GREEN colour (fin. 43)
BLACK colour (fin. 44)
WHITE colour (fin. 45)

Type	Description	Closing strength	Max. door width	Max. door weight	Unit weight 	 Pieces	ITEM			
							Type	Dim. Hand	Fin.	Pers. Spec.
	• MULTISTRENGTH VERSION • Standard arm	2÷4	850÷1100	80	1,800	1	1 71410 03 0 97			
	• MULTISTRENGTH VERSION • Standard arm • CE mark in compliance with the DIRECTIVE 89/106/CEE. • Voluntary ICIM certification issued by third party as provided for in the same UNI EN 1154 standards.	2÷4	850÷1100	80	1,800	1	1 71415 03 0 97			
		4÷6	1100÷1400	120	2,100	1	1 71415 05 0 97			
	• MULTISTRENGTH VERSION • Arm with hold-open	2÷4	850÷1100	80	2,100	1	1 71411 03 0 97			
	• MULTISTRENGTH VERSION • Arm with hold-open • Voluntary ICIM certification issued by third party as provided for in the same UNI EN 1154 standards.	2÷4	850÷1100	80	2,100	1	1 71416 03 0 97			
		4÷6	1100÷1400	120	2,300	1	1 71416 05 0 97			
	• MULTISTRENGTH VERSION • Built-in 90° hold-open	2÷4	850÷1100	80	1,800	1	1 71412 03 0 97			

Type	Description	Closing strength	Max. door width	Max. door weight	Unit weight Kg	Pieces	ITEM			
							Type	Dim.	Hand	Pers.
								Fin.	Spec.	
 	• FIXED STRENGTH • Slide track • Track without hold-open • Voluntary ICIM certification issued by third party as provided for in the same UNI EN 1154 standards.	1	750	20	1,800	1	1	71455 01	0	97
		2	850	40	2,100	1	1	71455 02	0	97
   	• FIXED STRENGTH • Slide track • Track without hold-open • CE mark in compliance with the DIRECTIVE 89/106/CEE • Voluntary ICIM certification issued by third party as provided for in the same UNI EN 1154 standards.	3	950	60	2,100	1	1	71455 03	0	97
 	• FIXED STRENGTH • Slide track • Track with hold-open • Voluntary ICIM certification issued by third party as provided for in the same UNI EN 1154 standards.	1	750	20	1,900	1	1	71456 01	0	97
		2	850	40	2,200	1	1	71456 02	0	97
		3	950	60	2,200	1	1	71456 03	0	97