

**Technical features:**

- Aluminium alloy monoblock body
- Steel arm with or without adjustable hold open
- Special oil bath steel spring
- Valve with thermostatic device

Operation:

- Closing strength 2÷6
- Adjustable closing speed
- Adjustable latch action
- Adjustable hold open (series 71516, 71611).



Supplied as standard:

- Fixing screws
- Template and assembly instructions

Finishes:

- Always specify the finish with the orders:
- Finishes available at no extra charge:
 - Champagne colour (fin. 87)
 - Dark brown colour (fin. 88)
 - Aluminium colour (fin. 97)
 - Dark bronze colour (fin. 99)
- Finishes available at an extra charge
 - Red colour (fin. 41)
 - Yellow colour (fin. 42)
 - Green colour (fin. 43)
 - Black colour (fin. 44)
 - White colour (fin. 45)

CISA *Professional*

Type	Description	Closing strength	Max. door width	Max. door weight	Unit weight Kg	Pieces	ITEM Type Dim. Hand Fin. Pers. Spec.
  	• MULTISTRENGTH VERSION • Arm without hold-open • CE mark in compliance with the DIRECTIVE 89/106/CEE • Voluntary ICIM certification issued by third party as provided for in the same UNI EN 1154 standards	2÷4	850÷1100	80	2,100	1	1 71510 03 0 97
		4÷6	1100÷1400	120	2,300	1	1 71510 05 0 97
 	• MULTISTRENGTH VERSION • Arm with hold-open • Voluntary ICIM certification issued by third party as provided for in the same UNI EN 1154 standards.	2÷4	850÷1100	80	2,300	1	1 71511 03 0 97
		4÷6	1100÷1400	120	2,500	1	1 71511 05 0 97