

**Technical features:**

- To be coupled with panic exit devices with side latch
- Rated voltage :
 - 12 and 24 V ac CE
 - 12 and 24 V dc CE
- Zinc plated steel case
- Lacquered aluminium alloy casing
- Chrome-plated aluminium alloy striker

Supplied as standard:

- Nylon spacers item 1.7089.02.0
- Fixing screws
- Instruction sheet


Finishes:

- STANDARD:
 - black case casing
- ON REQUEST (at an extra charge):

red case cover (fin. 41)
 yellow case cover (fin. 42)
 green case cover (fin. 43)
 white case cover (fin. 45)
 grey case cover (fin. 97)

Hand:

0 = Non-handed

Type	Description	Unit weight 	Pieces 	ITEM				
				Type	Dim.	Hand	Fin.	Spec.
	• Without hold-open catch mechanism • 12 V ac CE	0,500	1	1	07083	15	0	
	• Without hold-open catch mechanism • 12 V dc CE	0,500	1	1	07083	16	0	
	• Without hold-open catch mechanism • 24 V ac CE	0,500	1	1	07083	17	0	
	• Without hold-open catch mechanism • 1 microswitch • 12 V ac CE	0,500	1	1	07083	65	0	
	• Without hold-open catch mechanism • 1 microswitch • 12 V dc CE	0,500	1	1	07083	66	0	
	• Without hold-open catch mechanism • 1 microswitch • 24 V dc CE	0,500	1	1	07083	67	0	
	• Without hold-open catch mechanism • 2 microswitches • 12 V dc CE	0,500	1	1	07083	76	0	
	• Without hold-open catch mechanism • 2 microswitches • 24 V dc CE	0,500	1	1	07083	77	0	
	• With hold-open catch mechanism • 12 V ac CE	0,635	1	1	07083	25	0	
	• With live coils • 12 V dc	0,500	1	1	07083	35	0	
	• With live coils • 24 V dc	0,500	1	1	07083	36	0	