



Technical features:

- Zinc plated steel faceplate
- Zinc plated steel case
- Nickel-plated reversible steel latch
- Single throw (15 mm.) nickel-plated dead-bolt
- 9 mm. split follower
- Can be combined with the panic exit devices series 59600 and 59710

Hand:


0 = Non-handed



Cylinder to be ordered separately



Supplied as standard:

- Instruction sheet

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM				
								Type	Dim.	Hand	Fin.	Pers. Spec.
	• FOR SINGLE LEAF DOORS	1	92	24	25	0,610	1	1	43620	25	0	
	• Dead-locking latch and dead-bolt	1	92	24	30	0,655	1	1	43620	30	0	
	• A TYPE OPERATION	1	92	24	35	0,690	1	1	43620	35	0	
	• Inside: Panic exit device for opening Key for closing with dead-bolt	1	92	24	40	0,730	1	1	43620	40	0	
	• Outside: Key for activating latch and dead-bolt	1	92	24	45	0,780	1	1	43620	45	0	
	• B TYPE OPERATION	1	92	24	25	0,610	1	1	43630	25	0	
	• Inside: Panic exit device for opening Key for closing with dead-bolt and activating or disactivating external handle for latch operation	1	92	24	30	0,655	1	1	43630	30	0	
		1	92	24	35	0,690	1	1	43630	35	0	
		1	92	24	40	0,730	1	1	43630	40	0	
	• Outside: Key for closing with dead-bolt and activating or disactivating external handle for latch operation	1	92	24	45	0,780	1	1	43630	45	0	
	• C TYPE OPERATION	1	92	24	25	0,610	1	1	43631	25	0	
	• Inside: Panic exit device for opening Key for closing with dead-bolt and activating external handle for latch operation	1	92	24	30	0,655	1	1	43631	30	0	
		1	92	24	35	0,690	1	1	43631	35	0	
		1	92	24	40	0,730	1	1	43631	40	0	
	• Outside: Key for closing with dead-bolt and activating external handle for latch operation	1	92	24	45	0,780	1	1	43631	45	0	
	• D TYPE OPERATION	1	92	24	25	0,610	1	1	43632	25	0	
	• Inside: Panic exit device for opening Key for closing with dead-bolt	1	92	24	30	0,655	1	1	43632	30	0	
		1	92	24	35	0,690	1	1	43632	35	0	
		1	92	24	40	0,730	1	1	43632	40	0	
	• Outside: Key for closing with dead-bolt. The handle, with dead-bolt withdrawn, is activated for latch operation	1	92	24	45	0,780	1	1	43632	45	0	

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM			
								Type	Dim. Hand	Fin.	Pers. Spec.
	• FOR DOUBLE DOORS	1	92	24	25	0,560	1	1	43650	25	0
	• Panic lock series 43290 to be installed on secondary leaf	1	92	24	30	0,610	1	1	43650	30	0
	• Dead-bolt and latch	1	92	24	35	0,725	1	1	43650	35	0
	• A TYPE OPERATION	1	92	24	40	0,770	1	1	43650	40	0
	• Inside:	1	92	24	45	0,710	1	1	43650	45	0
	Panic exit device for opening										
	Key for closing with dead-bolt										
	• Outside:										
	Key for activating latch and dead-bolt										
	• B TYPE OPERATION	1	92	24	25	0,640	1	1	43660	25	0
	• Inside:	1	92	24	30	0,610	1	1	43660	30	0
	Panic exit device for opening	1	92	24	35	0,725	1	1	43660	35	0
	Key for closing with dead-bolt and activating or disactivating external handle for latch operation	1	92	24	40	0,760	1	1	43660	40	0
	• Outside:	1	92	24	45	0,710	1	1	43660	45	0
	Key for closing with dead-bolt and activating or disactivating external handle for latch operation										
	• C TYPE OPERATION	1	92	24	25	0,560	1	1	43661	25	0
	• Inside:	1	92	24	30	0,610	1	1	43661	30	0
	Panic exit device for opening	1	92	24	35	0,640	1	1	43661	35	0
	Key for closing with dead-bolt and activating external handle for latch operation	1	92	24	40	0,670	1	1	43661	40	0
	• Outside:	1	92	24	45	0,710	1	1	43661	45	0
	Key for closing with dead-bolt and activating external handle for latch operation										
	• D TYPE OPERATION	1	92	24	25	0,560	1	1	43662	25	0
	• Inside:	1	92	24	30	0,610	1	1	43662	30	0
	Panic exit device for opening	1	92	24	35	0,715	1	1	43662	35	0
	Key for closing with dead-bolt	1	92	24	40	0,760	1	1	43662	40	0
	• Outside:	1	92	24	45	0,710	1	1	43662	45	0
	Key for closing with dead-bolt. The handle, with dead-bolt withdrawn, is activated for latch operation										
	• FOR SECONDARY LEAF OF A DOUBLE DOOR	92	24	30	0,795	1	1	43690	30	0	
	• Panic lock series 43650, 43660, 43661, 43662 to be installed on secondary leaf	92	24	40	0,865	1	1	43690	40	0	
	• OPERATION:	92	24	60	1,020	1	1	43690	60	0	
	• Inside:panic exit device	92	24	75	1,100	1	1	43690	75	0	
	• ON REQUEST:										
	Extended bolts item 1.07088.03.0										
	Automatic dogging device item 1.07089.50.0										
	Top striker item 1.06141.80.0										