



Technical features:

- Zinc-plated steel faceplate
- Zinc-plated steel case
- Nickel-plated steel reversible latch
- Single throw (15 mm.) nickel-plated dead-bolt
- 8 mm. spindle
- To be coupled with panic exit devices series 59600 and 59710

Cylinder to be ordered separately





Supplied as standard:

- Instruction sheet

Hand:

0 = Non-handed

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM			
								Type	Dim.	Hand	Pers. Spec.
	• FOR SINGLE LEAF DOORS • Dead-bolt and latch with anti-picking device • A TYPE OPERATION • From inside: Panic exit device to open Key to close with dead-bolt • From outside: key to operate latch and dead-bolt	1	92	22	25	0,720	1	1	43220	25	0
		1	92	22	30	0,770	1	1	43220	30	0
		1	92	22	35	0,800	1	1	43220	35	0
	• B TYPE OPERATION • From inside: Panic exit device to open Key to close with dead-bolt and activate or deactivate the outside handle for latch operation • From outside: key to close with dead-bolt and activate or deactivate the outside handle for latch operation	1	92	22	25	0,720	1	1	43230	25	0
		1	92	22	30	0,770	1	1	43230	30	0
		1	92	22	35	0,800	1	1	43230	35	0
	• C TYPE OPERATION • From inside: Panic exit device to open Key to close with dead-bolt and activate the outside handle for latch operation • From outside: Key to close with dead-bolt and activate the outside handle for latch operation	1	92	22	25	0,720	1	1	43231	25	0
		1	92	22	30	0,770	1	1	43231	30	0
		1	92	22	35	0,800	1	1	43231	35	0
	• D TYPE OPERATION • From inside: Panic exit device to open Key to close with dead-bolt • From outside: Key to close with dead-bolt. The handle is activated by latch operation, with the dead-bolt withdrawn	1	92	22	25	0,720	1	1	43232	25	0
		1	92	22	30	0,770	1	1	43232	30	0
		1	92	22	35	0,800	1	1	43232	35	0

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM					
								Type	Dim.	Hand	Fin.	Pers.	Spec.
	• FOR DOUBLE LEAF DOORS	1	92	22	25	0,680	1	1	43250	25	0		
	• On the secondary leaf the item 43290 is to be installed	1	92	22	30	0,720	1	1	43250	30	0		
	• Dead-bolt and latch	1	92	22	35	0,750	1	1	43250	35	0		
	• A TYPE OPERATION												
	• From inside:												
	Panic exit device to open												
	Key to close with dead-bolt												
	• From outside:												
	Key to operate latch and dead-bolt												
	• B TYPE OPERATION	1	92	22	25	0,680	1	1	43260	25	0		
	• From inside:	1	92	22	30	0,720	1	1	43260	30	0		
	Panic exit device to open	1	92	22	35	0,750	1	1	43260	35	0		
Key to close with dead-bolt and activate or deactivate the outside handle for latch operation													
• From outside:													
key to close with dead-bolt and activate or deactivate the outside handle for latch operation													
• C TYPE OPERATION	1	92	22	25	0,680	1	1	43261	25	0			
• From inside:	1	92	22	30	0,720	1	1	43261	30	0			
Panic exit device to open	1	92	22	35	0,750	1	1	43261	35	0			
Key to close with dead-bolt and activate the outside handle for latch operation													
• From outside:													
Key to close with dead-bolt and activate the outside handle for latch operation													
• D TYPE OPERATION	1	92	22	25	0,680	1	1	43262	25	0			
• From inside:	1	92	22	30	0,720	1	1	43262	30	0			
Panic exit device to open	1	92	22	35	0,750	1	1	43262	35	0			
Key to close with dead-bolt													
• From outside:													
Key to close with dead-bolt. The handle is activated by latch operation, with the dead-bolt withdrawn													
	• FOR THE SECONDARY LEAF OF A DOUBLE DOOR	92	24	30	0,875	1	1	43290	30	0			
	• On the main leaf a lock series 43250, 43260, 43261, 43262 is to be installed	92	24	40	0,940	1	1	43290	40	0			
	• OPERATION:	92	22	60	1,100	1	1	43290	60	0			
	From inside with panic exit device												
• ON REQUEST:													
Extended bolts item 1.07088.03.0													
Dogging device item 1.07089.52.0													
Upper striker item 1.06141.80.0													