



Technical features:

- Black lacquered aluminium casing
- Red laquered aluminium bar
- Dead-locking, chrome-plated aluminium alloy latch

On request:

- Microswitch version (suffix LA)
- Hold-open device version (suffix FG)
- Fire resistant version with steel latch (suffix FR)




Finishes:

- STANDARD: black painted case, red painted bar
- ON REQUEST:
 - red case cover, black bar (fin. 41)
 - yellow case cover, black bar (fin. 42)
 - green case cover, black bar (fin. 43)
 - white case cover, black bar (fin. 45)

- grey case cover, grey bar (fin. 97)
- AVAILABLE BAR COLOUR FINISHES (at an extra charge):
 - anodized satin aluminium (suffix AL)
 - anodized satin bronze (suffix BR)
 - brass plated (suffix OT)
 - painted green (suffix VE)
 - painted white (suffix BI)
 - painted grey (suffix GR)

Standards:

- Certified in compliance with the European standard UNI/EN 1125 on escape doors equipment
- Voluntary ICIM certification issued by third party as provided for in the UNI EN 1125 standard.

Type	Description	L	Unit weight Kg	Pieces	ITEM				
					Type	Dim.	Hand	Fin.	Spec.
	• Lateral latch-bolt • SUPPLIED AS STANDARD: Strikers item 1.07072.20.0 and 1.07072.21.0 • ON REQUEST: Outside operation devices item 1.07077.28/29/46/47/48/49.0	1200	3,100	1	1	59800	10	0	
		840	3,800	1	1	59800	11	0	
	• MODULAR VERSION • Lateral latch-bolt which can be disactivated • SUPPLIED AS STANDARD: Strikers item 1.07072.20.0 and item 1.07072.21.0 • Can be used with: Pair of top/bottom latch-bolts item 1.07063.60.0 Pair of lateral latch-bolts item 1.07063.50.0 Pair of top/lateral latch-bolts item 1.07063.65.1/2 Pair of top/bottom dead-bolts item 1.07063.70.0 • ON REQUEST: Outside operation device item 1.07077.28/46/47/48.0	1300	3,100	1	1	59810	09	0	
		1200	3,100	1	1	59810	10	0	
		840	3,800	1	1	59810	11	0	
	• MODULAR VERSION • Must be used with: Pair of top/bottom latch-bolts item 1.07063.60.0 Pair of lateral latch-bolts item 1.07063.50.0 Pair of top/lateral latch-bolts item 1.07063.65.1/2 Pair of top/bottom dead-bolts item 1.07063.70.0 • ON REQUEST: Outside operation device item 1.07077.28/46/47/48.0	1200	2,500	1	1	59815	10	0	
		840	2,500	1	1	59815	11	0	