
RS3
Technical features:

- Patented system: key with incorporated mobile element
- Security Card: authorised duplication by Cisa only
- ICIM certified.
- 15 pins key bitting system
- CYLINDER
- brass body composed of two modular elements united by means of a special torsion resistant steel joint
- brass plugs with tearing resistant pin
- hardened steel pins
- hardened steel drivers
- stainless steel springs
- self-lubricating sintered steel projecting DIN cam

- KEY
- flat reversible keys, with incorporated mobile element
- in nickel silver
- numbered on key bow

Supplied as standard:

- 3 keys
- SECURITY CARD
- Fixing screw

On request:

- Cylinders with long key (ALI), compatible with protective roses (pers. CL)

Finishes:

- STANDARD: nickel-plated brass (fin. 12)
- ON REQUEST: polished brass (fin. 66)

Standards:

- Manufactured in conformity with EN 1303:
- Durability: grade 6 (100.000 cycles)
- Security: grade 5


Certifications:

- ICIM Certified: EN1303:98 1600015


Patents:

- EEC 0416500
- ALI is a registered shape, file number 4.137.601

Type	Description	Comm. dim.	Key item				Kg	Pieces	ITEM			
			L	A	B	Pins			Type	Dim.	Hand	Pers. Spec.



• Double cylinder

31 / 31	62,0	31,0	31,0	15	1	00700 01 0	0,260	1	1	OB310	07 0 12	
31 / 35	65,5	31,0	34,5	15	1	00700 01 0	0,270	1	1	OB310	26 0 12	
35 / 35	69,0	34,5	34,5	15	1	00700 01 0	0,279	1	1	OB310	13 0 12	
40 / 31	70,5	39,5	31,0	15	1	00700 01 0	0,290	1	1	OB310	12 0 12	
35 / 40	74,0	34,5	39,5	15	1	00700 01 0	0,305	1	1	OB310	28 0 12	
31 / 45	75,5	31,0	44,5	15	1	00700 01 0	0,305	1	1	OB310	27 0 12	
35 / 45	79,0	34,5	44,5	15	1	00700 01 0	0,315	1	1	OB310	19 0 12	
40 / 40	79,0	39,5	39,5	15	1	00700 01 0	0,315	1	1	OB310	18 0 12	
31 / 50	80,5	31,0	49,5	15	1	00700 01 0	0,320	1	1	OB310	17 0 12	
35 / 50	84,0	34,5	49,5	15	1	00700 01 0	0,330	1	1	OB310	31 0 12	
40 / 45	84,0	39,5	44,5	15	1	00700 01 0	0,324	1	1	OB310	30 0 12	
31 / 55	85,5	31,0	54,5	15	1	00700 01 0	0,327	1	1	OB310	33 0 12	
35 / 55	89,0	34,5	54,5	15	1	00700 01 0	0,345	1	1	OB310	32 0 12	
40 / 50	89,0	39,5	49,5	15	1	00700 01 0	0,338	1	1	OB310	21 0 12	
45 / 45	89,0	44,5	44,5	15	1	00700 01 0	0,345	1	1	OB310	29 0 12	
31 / 60	90,5	31,0	59,5	15	1	00700 01 0	0,342	1	1	OB310	20 0 12	
40 / 55	94,0	39,5	54,5	15	1	00700 01 0	0,360	1	1	OB310	42 0 12	
35 / 65	99,0	34,5	64,5	15	1	00700 01 0	0,375	1	1	OB310	22 0 12	
40 / 60	99,0	39,5	59,5	15	1	00700 01 0	0,375	1	1	OB310	25 0 12	
45 / 55	99,0	44,5	54,5	15	1	00700 01 0	0,372	1	1	OB310	43 0 12	
50 / 55	99,0	49,5	49,5	15	1	00700 01 0	0,372	1	1	OB310	23 0 12	
31 / 70	100,5	31,0	69,5	15	1	00700 01 0	0,390	1	1	OB310	24 0 12	
40 / 70	109,0	39,5	69,5	15	1	00700 01 0	0,402	1	1	OB310	35 0 12	
50 / 60	109,0	49,5	59,5	15	1	00700 01 0	0,402	1	1	OB310	36 0 12	
55 / 55	109,0	54,5	54,5	15	1	00700 01 0	0,402	1	1	OB310	70 0 12	
31 / 80	110,5	31,0	79,5	15	1	00700 01 0	0,406	1	1	OB310	37 0 12	
40 / 80	119,0	39,5	79,5	15	1	00700 01 0	0,440	1	1	OB310	60 0 12	


• Clutching system double cylinder


31 / 31	62,0	31,0	31,0	15	1	00700 01 0	0,255	1	1	OB311	07 0 12	
35 / 35	69,0	34,5	34,5	15	1	00700 01 0	0,279	1	1	OB311	13 0 12	
40 / 31	70,5	39,5	31,0	15	1	00700 01 0	0,284	1	1	OB311	12 0 12	
35 / 45	79,0	34,5	44,5	15	1	00700 01 0	0,310	1	1	OB311	19 0 12	
40 / 40	79,0	39,5	39,5	15	1	00700 01 0	0,310	1	1	OB311	18 0 12	
31 / 50	80,5	31,0	49,5	15	1	00700 01 0	0,314	1	1	OB311	17 0 12	
45 / 45	89,0	44,5	44,5	15	1	00700 01 0	0,338	1	1	OB311	29 0 12	

Type	Description	Comm. dim.				Key item			ITEM				
		L	A	B	Pins				Type	Dim.	Hand	Fin.	Pers. Spec.




- Single cylinder with adjustable cam in 8 position

31 / 10	41,0	31,0	10,0	15	1	00700 01 0	0,198	1	1	08314	02	0	12
35 / 10	44,5	34,5	10,0	15	1	00700 01 0	0,208	1	1	08314	07	0	12
40 / 10	49,5	39,5	10,0	15	1	00700 01 0	0,223	1	1	08314	03	0	12
45 / 10	54,5	44,5	10,0	15	1	00700 01 0	0,238	1	1	08314	08	0	12
50 / 10	59,5	49,5	10,0	15	1	00700 01 0	0,253	1	1	08314	04	0	12
60 / 10	69,5	59,5	10,0	15	1	00700 01 0	0,283	1	1	08314	05	0	12
65 / 10	74,5	64,5	10,0	15	1	00700 01 0	0,298	1	1	08314	21	0	12
70 / 10	79,5	69,5	10,0	15	1	00700 01 0	0,313	1	1	08314	06	0	12
80 / 10	89,5	79,5	10,0	15	1	00700 01 0	0,343	1	1	08314	20	0	12
95 / 10	103,5	93,5	10,0	15	1	00700 01 0	0,388	1	1	08314	13	0	12



- Double cylinder with thumb turn shaft
- ON REQUEST: Knobs
item 1.06353.00
item 1.06354.00

31 / 31	62,0	31,0	31,0	15	1	00700 01 0	0,271	1	1	08312	07	0	12
35 / 35	69,0	34,5	34,5	15	1	00700 01 0	0,292	1	1	08312	13	0	12
31 / 40	70,5	31,0	39,5	15	1	00700 01 0	0,295	1	1	08312	82	0	12
40 / 31	70,5	39,5	31,0	15	1	00700 01 0	0,295	1	1	08312	12	0	12
35 / 40	74,0	34,5	39,5	15	1	00700 01 0	0,305	1	1	08312	28	0	12
35 / 45	79,0	34,5	44,5	15	1	00700 01 0	0,320	1	1	08312	19	0	12
40 / 40	79,0	39,5	39,5	15	1	00700 01 0	0,320	1	1	08312	18	0	12
31 / 50	80,5	31,0	49,5	15	1	00700 01 0	0,324	1	1	08312	17	0	12
40 / 45	84,0	39,5	44,5	15	1	00700 01 0	0,334	1	1	08312	30	0	12
40 / 50	89,0	39,5	49,5	15	1	00700 01 0	0,350	1	1	08312	21	0	12
45 / 45	89,0	44,5	44,5	15	1	00700 01 0	0,350	1	1	08312	29	0	12
31 / 60	90,5	31,0	59,5	15	1	00700 01 0	0,354	1	1	08312	20	0	12
40 / 55	94,0	39,5	54,5	15	1	00700 01 0	0,354	1	1	08312	42	0	12
45 / 55	99,0	44,5	54,5	15	1	00700 01 0	0,354	1	1	08312	43	0	12
50 / 50	99,0	49,5	49,5	15	1	00700 01 0	0,354	1	1	08312	23	0	12
55 / 50	104,0	54,5	49,5	15	1	00700 01 0	0,354	1	1	08312	64	0	12
60 / 50	109,0	59,5	49,5	15	1	00700 01 0	0,415	1	1	08312	89	0	12
55 / 60	114,0	54,5	59,5	15	1	00700 01 0	0,415	1	1	08312	71	0	12
60 / 60	119,0	59,5	59,5	15	1	00700 01 0	0,415	1	1	08312	40	0	12
65 / 55	119,0	64,5	54,5	15	1	00700 01 0	0,415	1	1	08312	86	0	12



- Double cylinder with adjustable thumb turn shaft
- To be combined with inside rose item 1.06458.20
- ON REQUEST: Knobs
item 1.06353.00
item 1.06354.00

31 / 31	62,0	31,0	31,0	15	1	00700 01 0	0,306	1	1	08317	07	0	12
40 / 31	70,5	39,5	31,0	15	1	00700 01 0	0,340	1	1	08317	12	0	12
50 / 31	80,5	49,5	31,0	15	1	00700 01 0	0,370	1	1	08317	90	0	12
60 / 31	90,5	59,5	31,0	15	1	00700 01 0	0,405	1	1	08317	87	0	12
70 / 31	100,5	69,5	31,0	15	1	00700 01 0	0,398	1	1	08317	88	0	12