



Technical features:

- Patented system
- Registered key.
- 10 (6 active + 4 passive) pins key biting systems
- CYLINDER:
 - brass body
 - brass plug
- pins:
 - in wear resistant bronze
 - in hardened steel in first position
 - side stainless steel balls
- drivers:
 - in brass, cylindrical and mushroom-like for an antipicking function
 - in hardened steel in first position
- phosphor bronze spring

- KEY:
 - in nickel silver alloy
 - numbered on key bow

Supplied as standard:








- 3 keys
- Code Card
- Fixing screws

Finishes:

- Nickel-plated brass (fin. 12)

Patents:

- Registered key, file number 3.754.504

Type	Description	Door thickness Pins	Key item	Unit weight Kg	Pieces	ITEM			
						Type	Dim.	Hand	Pers. Spec.
	• Cylinder for padlocks: series 28052 - 28352 - 28552 • 2 keys • Pickled brass body • Complete with plate item 1.07573.07.1/2	6	1 00450 01 1	0,120	1	1	02652	01 0	
	• Cylinder for outside operation devices item 1.07077.29.0 • Sanded brass	6	1 00450 01 1	0,120	1	1	02652	10 0	
	• Cylinder for outside operation devices item 1.07077.29.0 • Sanded brass	6	1 00450 01 1	0,120	1	1	02652	11 0	
 	• Key removed in vertical position • Ring item 1.06021.10.0 • Cam item 1.06414.20.0 or item 1.06414.30.0, to be ordered separately	19	6 1 00450 01 1	0,195	1	1	72275	26 0 12	
 	• Microswitch (7 A, 250 V) with terminals to be welded • Automatic return to key extraction position (0) • Ring item 1.06021.10.0	19	6 1 00450 01 1	0,150	1	1	72276	01 0 12	
 	• Microswitch (7 A, 250 V) with terminals to be welded • Automatic return to key extraction position (0) • Ring item 1.06021.10.0	19	6 1 00450 01 1	0,145	1	1	72276	03 0 12	