


SBLOCK PVD
Technical features:

- Aluminium case cover and bar with PVD coating.
- Bar can be shortened up 300 mm
- Aluminium alloy lateral self locking latchbolt with PVD coating.

Supplied as standard:

- Strikers
- Fixing screws
- Installation and maintenance instruction sheet
- ICIM and CE Certification

On request:

- Version with microswitch (spec. LA)
- Version with hold open device (spec. FG)
- Fire version with steel latchbolts (spec. FR)

Finishes:




- Satin finish stainless steel (fin.C2)

Standards:

- CE mark in compliance with the DIRECTIVE 89/106/CEE issued by AENOR.
- Voluntary ICIM certification issued by third party as provided for in the UNI EN 1125 standard.

Hand:

0 = Non-hande

Type	Description	L	Unit weight Kg	Pieces	ITEM				
					Type	Dim.	Hand	Fin.	Pers. Spec.
	• Lateral latchbolt • SUPPLIED AS STANDARD: Strikers item 1.07072.70.0 and 1.07072.71.0 • ON REQUEST: Outside operation devices item 1.07077.28/29/46/47/48/49.0.C2	1200	3,100	1	1	59800	10	0	C2
		840	3,800	1	1	59800	11	0	C2
	• MODULAR VERSION • Lateral latch bolt wich can be deactivate • SUPPLIED AS STANDARD: strikers item 1.07072.70.0, 1.07072.71.0 • Can be used with: Pair of top/bottom latchbolts item 1.07063.60.0.C2 Pair of lateral latchbolts item 1.07063.50.0.C2 Pair of top/lateral latchbolts item 1.07063.65.1/2.C2 Pair of top/bottom deadbolts item 1.07063.70.0.C2 • ON REQUEST: Outside operation device 1.07077.28/46/47/48.0.C2	1200	3,100	1	1	59810	10	0	C2
		840	3,800	1	1	59810	11	0	C2
	• MODULAR VERSION • Can be used with: Pair of top/bottom latchbolts item 1.07063.60.0.C2 Pair of lateral latchbolts item 1.07063.50.0.C2 Pair of top/lateral latchbolts item 1.07063.65.1/2.C2 Pair of top/bottom deadbolts item 1.07063.70.0.C2 • ON REQUEST: Outside operation device 1.07077.28/46/47/48.0.C2	1200	2,500	1	1	59815	10	0	C2
		840	2,500	1	1	59815	11	0	C2