



**SBLOCK**PVD

**Technical features:**

- Aluminium case cover and bar with PVD coating.
- Bar can be shortened up 300 mm

**Supplied as standard:**

- Fixing screws
- Installation and maintenance instruction sheet
- ICIM and CE Certification

**On request:**

- Version with microswitch (spec. LA)

**Finishes:**

- Satin finish stainless steel (fin.C2)


**Standards:**

- CE mark in compliance with the DIRECTIVE 89/106/CEE issued by AENOR.

- Voluntary ICIM certification issued by third party as provided for in the UNI EN 1125 standard.

**Hand:**

0 = Non-handed

| Type                                                                              | Description                                                                                                                                                          | Spindle hole | L    |  Unit weight |  Pieces | ITEM |           |      |             |
|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|------|-------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|------|-----------|------|-------------|
|                                                                                   |                                                                                                                                                                      |              |      |                                                                                                 |                                                                                            | Type | Dim. Hand | Fin. | Pers. Spec. |
|  | • May be combined with panic function mortice locks series 43200, 43600, 52800, 52760, 52761 (for assembly with fire resistant locks specify Spec. FR in your order) | 8            | 1200 | 4,600                                                                                           | 1                                                                                          | 1    | 59710 10  | 0    | C2          |
|                                                                                   |                                                                                                                                                                      | 8            | 840  | 4,600                                                                                           | 1                                                                                          | 1    | 59710 11  | 0    | C2          |