

**Technical features:**

- Aluminium case cover and bar with PVD coating.
- Bar can be shortened up 300 mm

Supplied as standard:

- Fixing screws
- Installation and maintenance instruction sheet
- ICIM and CE Certification

On request:

- Version with microswitch (spec. LA)

Finishes:

- Satin finish stainless steel (fin.C2)


Standards:

- CE mark in compliance with the DIRECTIVE 89/106/CEE issued by AENOR.
- Voluntary ICIM certification issued by third party as provided for in the UNI EN 1125 standard

Hand:

0 = Non-handed

SBLOCKPVD

Type	Description	Spindle hole	L	Unit weight 	Pieces 	ITEM			
						Type	Dim.	Hand	Fin. Pers. Spec.
		9	1200	4,600	1	1	59710	00	0 C2
		9	840	4,600	1	1	59710	01	0 C2
		8/9	1200	4,600	1	1	59710	10	0 C2
		8/9	840	4,600	1	1	59710	11	0 C2

- May be combined with panic function fire resistant mortice locks series 43100

- May be combined with panic function mortice locks series 43200, 43600 and heavy duty mortice locks series 52760, 52761, 52840, 52842, 52844, 52860, 52862, 52864 (see locks for wooden doors)

- For assembly with fire resistant locks specify Spec. FR in your order