


SBLOCK
Technical features:

- Black lacquered aluminium casing
- Internal, zinc plated steel components, suitable for fire doors
- Bar in aluminium alloy, can be shortened to 300 mm

Supplied as standard:

- Fixing screws
- Installation templates
- Instruction sheet

On request:

- Version with microswitch (LA suffix)

Finishes:

- STANDARD: black case, red bar
- ON REQUEST (at an extra charge): red case, black bar (fin. 41)

- yellow case, black bar (fin. 42)
- green case, black bar (fin. 43)
- white case, black bar (fin. 45)
- grey case, grey bar (fin. 97)

AVAILABLE BAR COLOUR FINISHES

(at an extra charge):


- anodized, satin aluminium (AL suffix)
- anodized, satin bronze (BR suffix)
- brass plated (OT suffix)
- painted green (VE suffix)
- painted white (BI suffix)
- painted grey (GR suffix)

Standards:

- Manufactured in conformity with the European standard UNI/EN 1125 on escape doors equipment

Hand:

0 = Non-handed

Type	Description	Spindle hole L	 Unit weight	 Pieces	ITEM				
					Type	Dim.	Hand	Fin.	Spec.
	• May be combined with panic locks series 43100	9	1200	4,600	1	1	59710	00	0
		9	840	4,600	1	1	59710	01	0
	• May be combined with panic function mortice locks series 43200, 43600 and heavy duty mortice locks series 52760, 52761, 52840, 52842, 52844, 52860, 52862, 52864 (see locks for wooden doors) • For assembly with fire resistant locks specify Spec. FR in your order	8/9	1200	4,600	1	1	59710	10	0
		8/9	840	4,600	1	1	59710	11	0